

How FLiDARs can enrich your Metocean datasets and reduce your project development costs





Agenda

- 1. Data
- 2. Purposes of a FLiDAR® campaign
- 3. Project timelines
- 4. FLiDAR® performance verification results
- 5. FLiDAR short video
- 6. Lessons learned
- 7. Introduction to AXYS






Met Ocean Data




Modelos Durante el Ciclo de Vida de un Proyecto

Environmental Impact Analysis / Energy Yield Studies / Shear Studies / Turbulence Intensity
Calculations / Weather Hindcasting / Sea-State Monitoring / Pre-Construction Baselining / Weather
Forecasting Physical Asset Design / Power Curve Analysis / Asset Condition Monitoring / Bird/Bat
Monitoring / Scour Monitoring / Fish and Flore Identification Studies / End of Life Assessment

Current High Level Data Tools



Satellite Data / Models



Hindcasting Data / Models



Purposes of a FLiDAR®



Campaign Why do you need FLiDAR measurements?

- 1. For wind data which will be used in the annual energy yield predictions, for wind turbine selection and for operations planning (both installation and O&M)
- 2. For sea state data which depending on the site can be the more important design parameter for the tower and substructure as well as for operations planning
- 3. Other environmental monitoring e.g., birds, bats, sea mammals

Why choose a FLiDAR over a met mast?

- FLiDAR® buoys can typically be deployed within a few months
- Permitting FLiDAR® buoys is typically more straightforward
- FLiDAR® buoys are typically 10x less expensive than a met mast option



Overall Eolic Project Timeline

- Hind cast modeling
- Site characteristics
- Wind farm design
- Wind assessment
- Risk assessment
- Enviro assessment
- Real-time/forecast sea state during Construction/ O&M
- HSE/O&M contract compliance monitoring
- Turbine performance monitoring

Plan > Approve

Finance

Construct

Operate

Retire Replace

Wind Assessment Timeline



Schedule variations could be expected for -

- Time to fill wind speed bins during per campaign performance verification
- Weather delays
- Vessel availability
- Permitting delays


/ Pre

Pre Validation Measurement Campaign



has 19 Met Mast Validations Complete or Underway

Proven accurate in a wide variety of sea states





AXYS FLiDAR Solutions are Consistently Accurate to Industry Standards

Table 2: Example of Recent AXYS FliDAR WindSentinel Validation Campaign Against Met Mast

| 88m | | | 68m | | | 48m | | | |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| | r2 | slope | offset | r2 | slope | offset | r2 | slope | offset |
| Unit 1 | 0.9825 | 1.0047 | 4.0577 | 0.9895 | 1.0264 | 4.0577 | 0.9895 | 1.0271 | 2.4223 |
| Unit 2 | 0.9846 | 1.0029 | 3.4251 | 0.9889 | 1.0267 | 4.4378 | 0.9924 | 1.0262 | 1.8153 |
| Unit 3 | 0.9800 | 1.0032 | 5.2399 | 0.9838 | 1.0256 | 5.6647 | 0.9871 | 1.0281 | 3.6889 |
| Unit 4 | 0.9777 | 1.0039 | 4.0265 | 0.9823 | 1.0288 | 5.0286 | 0.9827 | 1.0272 | 2.2357 |

KPI-AC passed best practice


KPI-AC passed minimum


KPI-AC failed



Accuracy - Results of Long-Term Validations


Top height wind speed correlation plots for five month campaign






No Degradation in Measurement Accuracy Over Time

Top height wind direction correlation plots for five





Source: DNVGL analysis



The FLIDAR WindSentinel performs in extreme weather conditions for extended

West of Duddon Sands 6-mo campaign Max 10-minute average wind speed measured by

- the top cup 29.8 m/s
- Significant wave heights as measured from the buoy were $H_s > 5 \text{ m}$ with a max wave of 9.4 m¹
- Tidal difference was 10.2 m

| FINO 1 Validation 5 | 5-mo campaign |
|---------------------|---------------|
|---------------------|---------------|

- Max 10-minute average wind speed measured by the top cup - **26.4 m/s**
- Significant wave heights as measured from the buoy were $H_s > 5.9 \text{ m}$ with a max wave of 10.7 m¹

| | WS Max | WRMM FliDAR | | |
|---|-------------|-------------|--|--|
| | Level / [m] | WS [m/s] | | |
| | 55 | 28,05 28,10 | | |
| l | 70 | 28,85 28,99 | | |
| | 85 | 29,78 30,02 | | |

| WS Max | Cup | ZP1 | ZP2 |
|-------------|-------|----------|-------|
| Level / [m] | | WS [m/s] | |
| 103 | 26,42 | 25,01 | 26,57 |
| 90 | 26,07 | 25,57 | 25,72 |
| 80 | 25,71 | 25,56 | 25,14 |
| 60 | 25,13 | 25,01 | 24,59 |
| 40 | 24,40 | 23,31 | 24,29 |

Source: DNVGL analysis

Note: AXYS measures waves using a 30-minute interval

The AXYS team has planned, resourced and executed hundreds of offshore FLiDAR operations – commissioning, deployments, recoveries, maintenance, service at sea from dozens of ports around the world, on dozens of different vessels.

Our data specialists have supported most of the worlds leading 3rd party engineers and bank technical advisors – we understand how to make a campaign investment-grade.



Months in Campaign

50.0

Validation Campaigns




Dual LiDAR Benefits

AXYS FLiDAR WindSentinel™

supports single, dual ZX Lidar or

Windcube LiDARs (or mixed)
Improved data availability – Eliminate
interruptions and extra costs in the case of
LIDAR failure at-sea

- 2. Confidence in data accuracy— constant correlation of data to confirm data quality
- 3. Optimized maintenance cycles by using mixed life units
- 4. Higher data certainty consistent link to original reference as well as potential reduction of systemic uncertainty






Multiple Layers of Redunda

LiDARs, orientation sensors, data storage, power systems and more


Reduce the chance that typical issues in these regions impact our ability to collect your valuable measurement campaign data

- Sensor OEM failure
- Weather damage
- Interference




AXYS

Sophisticated Data Network and 24/7 Quality Monitoring





The Evolution of Standards in Floating LiDAR





AXYS FLiDAR WindSentinel in the North Sea at FINO 1 Met Mast


https://youtu.be/5V8I0wPCq-M





Lessons learned

- 1. Try to plan deployment in the moderate weather seasons
- 2. Give as much notice as possible to the contractor
- 3. Start permitting as quickly as possible
- 4. Ensure your FLiDAR supplier has a reputable mooring engineering design team



OUR COMPANY



AXYS

Founded 1974

Headquartered in Sidney, British Columbia on Vancouver Island, Started to support environmental consulting for the artic.



1987 First Met Ocean buy NOMAD





AXYS integrates LiDAR into its Nomad floating platform.







development of the proprietary wave technology and in 2011 launches the only Wave Buoy that measures waves and currents





acquires lead competitor FLiDAR NV and their floating

LiDAR device with a four-meter hull



2019 AXYS WindSentinel to Reach


AXYS embarks on project to be the firs grating LiPA3

device to reach Carbon Trust Roadmap Stage 3

classification



Core





ACCURATE, RELIABLE, COMPLETE WIND AND METOCEAN DATASETS



ROBUST REDUNTANT SYSTEM 600+ Commercial Campaign Months *As of August 2019



Verified Uncertainty Rates
BELOW 4%

Proven rugged buoy design performs even in the harshest marine environments

ENEFITS OF AXYS METOCEAN CAMPAIGNS



High Data Availability Track Record



Multiple Data

Quality Controls





Proven Rugged SolutionsMarinized for harsh conditions



Full Offshore OperationsDeployment/Recovery
Support and Maintenance



Experienced Field Teams North America, Europe, Asia



ISO 9001, 45001, 14001



